



Flooring Options*

Standard

- Allowable stationary load of 600 pounds per sq. ft. when placed on a continuous concrete slab**
- Extruded Polystyrene insulation
- 22-gauge stainless steel interior

Reinforced

- Allowable stationary load of 1,000 pounds per sq. ft. when placed on a continuous concrete slab**
- Extruded Polystyrene insulation
- Wood reinforced
- 22-gauge stainless steel interior

Titan

- Allowable stationary load of 5,000 pounds per sq. ft. when placed on a continuous concrete slab**
- Extruded Polystyrene insulation
- Wood reinforced with added insulated tubing
- 22-gauge stainless steel interior

Diamond Tread Floor available for onsite installation



Ramps

Ramps are customized to fit your doorway for easy access in and out of your unit.

- Interior 24"-48"
- Exterior Coated Safety Yellow 24"-48"



*Verify that building is transit level prior to installing walk-ins; notify Owner and Architect if sub-floor ventilation or heating is required for walk-in freezers; Dealer or Consultant to verify that sub-floor installation conditions are acceptable prior to installing floor and box. Exposed Prefabricated Floor: Prefabricated refrigerator or freezer floor panels must have R-28 rating or greater

** U.S. Cooler floors are not designed for the use of forklifts, pallet jacks or hard-wheeled carts. Damage caused by this usage will void the panel warranty.



| 401 DELAWARE ST. QUINCY, IL 62301 |
| 800.521.2665 | WWW.USCOOLER.COM |