

BLBT.R21217 - Building Units

Building Units

U S COOLER
 325 PAYSON AVE
 QUINCY, IL 62301-4849 United States

R21217

Panels consisting of foamed plastic core having steel facing on both sides.

	Core Material	4 in.Thick Painted or Unpainted Steel Finished Panel
Flame spread	5#	70
Smoke developed	175#	Over 500

#Flame spread and smoke developed recorded while material remained in the original test position. Ignition of molten residue on the furnace floor resulted in flame travel equivalent to calculated flame spread 75-100 and smoke developed of over 500.

	Core Material	4 in.Thick Painted or Unpainted Steel Finished Panel
Flame spread	20#	90
Smoke developed	300#	Over 500

#Flame spread and smoke developed recorded while material remained in the original test position. Ignition of molten residue on the furnace floor resulted in flame travel equivalent to calculated flame spread 180 and smoke developed of over 500.

	Core Material	4 in.Thick Painted or Unpainted Steel Finished Panel
Flame spread	5#	70
Smoke developed	165#	Over 500

#Flame spread and smoke developed recorded while material remained in the original test position. Ignition of molten residue on the furnace floor resulted in flame travel equivalent to calculated flame spread 90 and smoke developed of over 500.

	Core Material	4 in.Thick Painted or Unpainted Aluminum Skinned Panel
Flame spread	5#	45
Smoke developed	165#	Over 500

#Flame spread and smoke developed recorded while material remained in the original test position. Ignition of molten residue on the furnace floor resulted in flame travel equivalent to calculated flame spread 125 and smoke developed of over 500.

Cookies on UL Solutions

Cookies Settings

Accept All Cookies

features and to analyze our traffic. We also share information about your use

of our site with our social media, advertising and analytics partners. [Learn](#)

[more](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [**Learn more**](#)